Dam:	Ballikaya	Country	Turkey
River	Mudurnu	40°34'50.29"N 30°41'9.36"E	40.580635 30.685934
Owner/Client	DSI - State Hydraulic Works		
Designer/Engineer	*Unknown*		
Contractor	Abdurrahman Çorum-Elif Mühendislik Makina Sanayi Ve Ticaret İs Ortaligi		

Purpose (code)	W
Site start	01.01.2013
RCC start	01.01.2015
RCC completion	31.12.2020
Site completion	31.12.2023
Height (m)	98
Length (m)	357
Volume of RCC (m^3x10^3)	800
Total volume (m^3x10^3)	*Unknown*
Reservoir capacity (m^3x10^6)	143
Upstream slope	0.10 0.35
Forming of upstream face (code)	(1)
Downstream slope	0.70
Forming of downstream face (code)	(1)
Spillway slope	*Unknown*
Forming of spillway face (code)	*Unknown*
Depth of layers (mm)	300
Depth of lifts (mm)	300
Cement content (kg/m^3)	63 83
Pozzolan content (kg/m^3)	63 83
Code for pozzolan	*Unknown*
RCCDAM Unique Serial No.	RCCDAM1136

Guide to Abbreviations

Purpose

E	Environmental
F	Flood control
G	Groundwater recharge
H	Flood control
I	Irrigation
N	Navigation
P	Pollution control
R	Recreation
W	Water supply

Facing method

(1)	Traditional concrete against formwork
(2)	Traditional concrete against formwork with external geomembrane
(3)	RCC against formwork
(4)	RCC against formwork with external geomembrane
(5)	Traditional concrete against precast concrete panels
(6)	Traditional concrete against precast concrete panels with geomembrane
(7)	RCC against precast concrete panels
(8)	RCC against precast concrete panels with geomembrane
(9)	RCC against precast concrete panels with hot poured membrane
(10)	RCC against precast concrete blocks
(11)	Reinforced conventional concrete cast before RCC placement
(12)	Reinforced conventional concrete cast after RCC placement
(13)	Reinforced concrete cast against precast units or slip-formed facing elements
(14)	Slip-formed/extruded facing elements
(15)	RCC supported by fill shoulders
(16)	Mechanically compacted unformed face of RCC
(17)	Unformed face of RCC
'	GEVR/GE-RCC
*	Stepped face

Pozzolans

(-)	No Pozzolan Used
(C)	High-lime flyash (ASTM Class C)
(F)	Low-lime flyash (ASTM Class F)
(M)	Milled sand
(N)	Natural pozzolan (ASTM Class N)
(R)	ROLAC (mixture of flyash and slag with or without limestone fines)
(S)	Ground-granulated blast-furnace slag
(L)	Mixture of GGBFS and limestone fines