

Dam: Enlarged Cotter

Country: Australia

River: Cotter

35°19'12.51"S 148°56'24.02"E

-35.320141 148.940002

Owner/Client: Icon Water (formerly ACTEW Corp.)

Designer/Engineer: GHD Pty. Ltd.

Contractor: Bulk Water Alliance (Abigroup/John Holland JV)

Purpose (code): W

Site start: 01.10.2009

RCC start: 01.08.2011

RCC completion: 01.12.2012

Site completion: 01.08.2013

Height (m): 87

Length (m): 350

Volume of RCC (m³x10³): 369

Total volume (m³x10³): 400

Reservoir capacity (m³x10⁶): 78

Upstream slope: V

Forming of upstream face (code): (3')

Downstream slope: 0.75

Forming of downstream face (code): (3') *

Spillway slope: 0.75

Forming of spillway face (code): (3') *

Depth of layers (mm): 300
400

Depth of lifts (mm): 300
400

Cement content (kg/m³): 75

Pozzolan content (kg/m³): 120

Code for pozzolan: (F)

RCCDAM Unique Serial No.: RCCDAM0548

Under Construction



RCCDAM0548UC

Completed Dam



RCCDAM0548CD

Google Earth



RCCDAM0548GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines