

Dam: Igarapeba

Country Brazil

River Una

8°48'08.5"S 35°53'8.46"W

-8.802361 -35.885681

Owner/Client Secretária de Desenvolvimento Econômico

Designer/Engineer *Unknown*

Contractor *Unknown*

Purpose (code) W

Site start 01.01.2013

RCC start 01.01.2014

RCC completion 31.12.2015

Site completion 31.12.2015

Height (m) 61

Length (m) *Unknown*

Volume of RCC (m³x10³) *Unknown*

Total volume (m³x10³) *Unknown*

Reservoir capacity (m³x10⁶) 69

Upstream slope

Forming of upstream face (code)

Downstream slope

Forming of downstream face (code)

Spillway slope

Forming of spillway face (code)

Depth of layers (mm)

Depth of lifts (mm)

Cement content (kg/m³)

Pozzolan content (kg/m³)

Code for pozzolan

RCCDAM Unique Serial No. RCCDAM0920

Completed Dam



RCCDAM0920CD

Google Earth



RCCDAM0920GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines