

Dam: Jim Wilson (formerly Town Wash Detention)

Country USA

River Town Wash

36°49'32.46"N 114°04'22.48"W

36.825684 -114.072914

Owner/Client Town of Mesquite, Nevada

Designer/Engineer CH2M - Hill, Redding, California

Contractor Progressive Contracting Inc.

Purpose (code) F

Site start 01.01.1992

RCC start 01.03.1992

RCC completion 31.05.1992

Site completion 30.06.1992

Height (m) 18

Length (m) 264

Volume of RCC ( $m^3 \times 10^3$ ) 43

Total volume ( $m^3 \times 10^3$ ) 45

Reservoir capacity ( $m^3 \times 10^6$ ) *Unknown*

Upstream slope V

Forming of upstream face (code) (14)

Downstream slope 1.50

Forming of downstream face (code) (3)

Spillway slope 1.50

Forming of spillway face (code) (3) \*  
(17) \*

Depth of layers (mm) 200

Depth of lifts (mm) 200

Cement content ( $kg/m^3$ ) 107

Pozzolan content ( $kg/m^3$ ) 71

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0098

## Under Construction



RCCDAM0098UC

## Completed Dam



RCCDAM0098CD

## Google Earth



RCCDAM0098GE

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines