

Dam: Kasegawa

Country Japan

River Kase

33°23'21.44"N 130°13'0.83"E

33.38929 130.216904

Owner/Client Ministry of Land, Infrastructure, Transport and Tourism

Designer/Engineer Yachiyo Engineering Co. Ltd.

Contractor Kajima Construction Co. Ltd., Aoki-Asunaro Construction Co. Ltd. and Matsuo Construction Co. Ltd.,

Purpose (code) F H I W

Site start 01.02.2005

RCC start 01.10.2007

RCC completion 30.06.2009

Site completion 31.03.2012

Height (m) 99

Length (m) 456

Volume of RCC (m³x10³) 830

Total volume (m³x10³) 948

Reservoir capacity (m³x10⁶) 71

Upstream slope V
0.60

Forming of upstream face (code) (1)
(1)

Downstream slope 0.75

Forming of downstream face (code) (1)

Spillway slope 0.75

Forming of spillway face (code) (1)

Depth of layers (mm) 250

Depth of lifts (mm) 1000

Cement content (kg/m³) 84

Pozzolan content (kg/m³) 36

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0444

Completed Dam



RCCDAM0444CD

Google Earth



RCCDAM0444GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines