

Dam: Kheng Grou

Country Morocco

River Kheng Grou

32°20'46.8"N 3°5'34.32"W

32.346333 -3.092866

Owner/Client Direction des Aménagements Hydrauliques

Designer/Engineer Novec

Contractor Bioui Travaux

Purpose (code) F I W

Site start 01.04.2022

RCC start 01.01.2024

RCC completion 31.08.2026

Site completion 31.12.2026

Height (m) 79

Length (m) 196

Volume of RCC (m³x10³) 550

Total volume (m³x10³) 55

Reservoir capacity (m³x10⁶) 1070

Upstream slope 0.20

Forming of upstream face (code) (5)

Downstream slope 1.00

Forming of downstream face (code) (5)

Spillway slope 1.00

Forming of spillway face (code) (13)

Depth of layers (mm) 300

Depth of lifts (mm) 3000

Cement content (kg/m³) Unknown

Pozzolan content (kg/m³) Unknown

Code for pozzolan Unknown

RCCDAM Unique Serial No. RCCDAM0887

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines