

Dam: Linhekou

Country: China

River: Lanhe

32°18'38.08"N 108°56'17.70"E

32.310577 108.938248

Owner/Client: Shaanxi Lan River Hydropower Development Corporation

Designer/Engineer: Northwest Institute of Investigation and Design of Hydropower, Xi'an, Shaanxi Province

Contractor: 4th Construction Bureau

Purpose (code): H I

Site start: 01.01.1999

RCC start: 23.12.2001

RCC completion: 01.06.2003

Site completion: 31.12.2004

Height (m): 100

Length (m): 311

Volume of RCC (m³x10³): 229

Total volume (m³x10³): 293

Reservoir capacity (m³x10⁶): 147

Upstream slope: curve

Forming of upstream face (code): (3')

Downstream slope: curve

Forming of downstream face (code): (3')

Spillway slope: ogee

Forming of spillway face (code): (1)

Depth of layers (mm): 300

Depth of lifts (mm): 3000

Cement content (kg/m³): 74
66

Pozzolan content (kg/m³): 111
111

Code for pozzolan: (F)

RCCDAM Unique Serial No.: RCCDAM0294

Completed Dam



RCCDAM0294CD

Google Earth



RCCDAM0294GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines