

Dam: Marathia

Country: Greece

River: Marathia

37°28'12.66"N 25°21'28.22"E

37.470184 25.35784

Owner/Client: Ministry of Agriculture

Designer/Engineer: Hydrosystems Ltd.

Contractor: K.J. Sarantopoulos S.A. - S.A.

Purpose (code): I W

Site start: 25.11.1992

RCC start: 01.12.1992

RCC completion: 30.04.1993

Site completion: 30.06.1993

Height (m): 28

Length (m): 265

Volume of RCC (m<sup>3</sup>x10<sup>3</sup>): 31

Total volume (m<sup>3</sup>x10<sup>3</sup>): 48

Reservoir capacity (m<sup>3</sup>x10<sup>6</sup>): 3

Upstream slope: 0.50

Forming of upstream face (code): (13)

Downstream slope: 0.50

Forming of downstream face (code): (10)

Spillway slope: 0.50

Forming of spillway face (code): (13)

Depth of layers (mm): 200 - 300

Depth of lifts (mm): 200 - 300

Cement content (kg/m<sup>3</sup>): 55

Pozzolan content (kg/m<sup>3</sup>): 15

Code for pozzolan: (N)

RCCDAM Unique Serial No.: RCCDAM0117

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines