

Dam: Narli

Country Turkey

River Göksu

40°14'40"N 29°17'53"E

40.244446 29.298056

Owner/Client Akxa Energy Production Trade and Industry Co. Inc.

Designer/Engineer Unknown

Contractor Unknown

Purpose (code) H

Site start 01.01.2016

RCC start 01.01.2017

RCC completion 31.12.2018

Site completion 31.12.2019

Height (m) 47

Length (m) 153

Volume of RCC (m³x10³) 49

Total volume (m³x10³) 68

Reservoir capacity (m³x10⁶) 27

Upstream slope Unknown

Forming of upstream face (code) (14)

Downstream slope Unknown

Forming of downstream face (code) (14)

Spillway slope Unknown

Forming of spillway face (code) Unknown

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 65

Pozzolan content (kg/m³) 50

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0483

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines