

Dam: Quail Creek South

Country USA

River Quail Creek

37°10'34.76"N 113°23'34.62"W

37.176323 -113.392952

Owner/Client Washington County Water Conservancy District

Designer/Engineer Morrison-Knudsen Engineers

Contractor ASI-RCC Inc.

Purpose (code) W

Site start 01.02.1990

RCC start 28.03.1990

RCC completion 25.05.1990

Site completion 31.08.1990

Height (m) 42

Length (m) 610

Volume of RCC (m³x10³) 130

Total volume (m³x10³) 150

Reservoir capacity (m³x10⁶) 50

Upstream slope V

Forming of upstream face (code) (1)

Downstream slope V
0.85

Forming of downstream face (code) (1)
(17)

Spillway slope conduit

Forming of spillway face (code) Unknown

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 80

Pozzolan content (kg/m³) 53

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0064

Under Construction



RCCDAM0064UC

Completed Dam



RCCDAM0064CD

Google Earth



RCCDAM0064GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines