

Dam: Queiles y Val

Country Spain

River Val

41°52'34.65"N 1°47'12.90"W

41.876293 -1.786917

Owner/Client Confederación Hidrográfica del Ebro

Designer/Engineer Unknown

Contractor UTE Idecon S.A, Lain S.A. and Obrascon S.A.

Purpose (code) F

Site start 01.01.1993

RCC start 07.10.1995

RCC completion 31.05.1997

Site completion 31.12.1997

Height (m) 82

Length (m) 375

Volume of RCC (m³x10³) 480

Total volume (m³x10³) 520

Reservoir capacity (m³x10⁶) 25

Upstream slope V
0.33

Forming of upstream face (code) (1)
(1)

Downstream slope 0.80

Forming of downstream face (code) (5)

Spillway slope 0.80

Forming of spillway face (code) (1)

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content (kg/m³) 80

Pozzolan content (kg/m³) 145

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0182

Under Construction



RCCDAM0182UC

Completed Dam



RCCDAM0182CD

Google Earth



RCCDAM0182GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines