

Dam: Suçati

Country Turkey

River Güredin Creek

37°45'40.59"N 36°43'58.97"E

37.761276 36.733047

Owner/Client ERE Electricity Co.

Designer/Engineer EN-SU Engineering

Contractor ERE Engineering Co.

Purpose (code) H

Site start 04.01.1998

RCC start 23.02.1999

RCC completion 06.10.1999

Site completion 25.10.1999

Height (m) 36

Length (m) 192

Volume of RCC ( $m^3 \times 10^3$ ) 55

Total volume ( $m^3 \times 10^3$ ) 60

Reservoir capacity ( $m^3 \times 10^6$ ) 9

Upstream slope V

Forming of upstream face (code) (7)

Downstream slope 0.80

Forming of downstream face (code) (7)

Spillway slope 0.80

Forming of spillway face (code) (12)

Depth of layers (mm) 300

Depth of lifts (mm) 300

Cement content ( $kg/m^3$ ) 50

Pozzolan content ( $kg/m^3$ ) 100

Code for pozzolan (S)

RCCDAM Unique Serial No. RCCDAM0220

## Completed Dam



RCCDAM0220CD

## Google Earth



RCCDAM0220GE

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines