

Dam: Tannur

Country Jordan

River Wadi al Hasa

30°58'21.21"N 35°42'48.68"E

30.972557 35.713524

Owner/Client Jordan Valley Authority, Ministry of Water and Irrigation

Designer/Engineer Howard Humphreys

Contractor Bec Frères S.A./Campenon Bernard SGE JV

Purpose (code) I

Site start 01.02.1999

RCC start 01.12.1999

RCC completion 19.12.2000

Site completion 30.09.2001

Height (m) 60

Length (m) 270

Volume of RCC (m³x10³) 250

Total volume (m³x10³) 250

Reservoir capacity (m³x10⁶) 17

Upstream slope V
1.00

Forming of upstream face (code) (3')

Downstream slope 0.80

Forming of downstream face (code) (3') *

Spillway slope 0.80

Forming of spillway face (code) (3') *

Depth of layers (mm) 300

Depth of lifts (mm) 1200

Cement content (kg/m³) 125
120

Pozzolan content (kg/m³) 75
50

Code for pozzolan (N)

RCCDAM Unique Serial No. RCCDAM0243

Under Construction



RCCDAM0243UC

Completed Dam



RCCDAM0243CD

Google Earth



RCCDAM0243GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines