

Dam: Taquarembó

Country Brazil

River Taquarembó

30°47'35.82"S 54°35'32.68"W

-30.793282 -54.592411

Owner/Client Estado

Designer/Engineer *Unknown*

Contractor *Unknown*

Purpose (code) W

Site start 01.05.2008

RCC start 01.01.2010

RCC completion 31.12.2019

Site completion 31.12.2020

Height (m) 33

Length (m) 330

Volume of RCC ( $m^3 \times 10^3$ ) *Unknown*

Total volume ( $m^3 \times 10^3$ ) *Unknown*

Reservoir capacity ( $m^3 \times 10^6$ ) *Unknown*

Upstream slope *Unknown*

Forming of upstream face (code) *Unknown*

Downstream slope *Unknown*

Forming of downstream face (code) *Unknown*

Spillway slope *Unknown*

Forming of spillway face (code) *Unknown*

Depth of layers (mm) *Unknown*

Depth of lifts (mm) *Unknown*

Cement content ( $kg/m^3$ ) *Unknown*

Pozzolan content ( $kg/m^3$ ) *Unknown*

Code for pozzolan *Unknown*

RCCDAM Unique Serial No. RCCDAM1060

## Under Construction



RCCDAM1060UC

## Completed Dam



RCCDAM1060CD

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines