

Dam: Tomisato

Country Japan

River Douzan

33°53'0.75"N 133°28'46.76"E

33.883541 133.47966

Owner/Client Water Resources Development Public Corporation

Designer/Engineer Water Resources Development Public Corporation

Contractor Ohbayashi Co Ltd, Sumitomo Construction Ltd and Morimoto Co Ltd J.V.

Purpose (code) F I W

Site start 01.02.1992

RCC start 01.01.1995

RCC completion 28.02.1997

Site completion 31.03.2000

Height (m) 111

Length (m) 250

Volume of RCC ($m^3 \times 10^3$) 355

Total volume ($m^3 \times 10^3$) 510

Reservoir capacity ($m^3 \times 10^6$) 53

Upstream slope V

Forming of upstream face (code) (1)

Downstream slope 0.76

Forming of downstream face (code) (1)

Spillway slope 0.76

Forming of spillway face (code) (1)

Depth of layers (mm) 250

Depth of lifts (mm)
750
1000

Cement content (kg/m^3)
84
72

Pozzolan content (kg/m^3)
36
48

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0179

Completed Dam



RCCDAM0179CD

Google Earth



RCCDAM0179GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines