

Dam: Kabagawa

Country Japan

River Kaba

34°9'12"N 134°6'21"E

34.153332 134.105835

Owner/Client Kagawa Prefecture

Designer/Engineer Nippon Koei Co. Ltd.

Contractor Taisei Corporation

Purpose (code) F W

Site start 01.10.2014

RCC start 01.11.2016

RCC completion 31.05.2019

Site completion 30.09.2020

Height (m) 89

Length (m) 266

Volume of RCC (m³x10³) 242

Total volume (m³x10³) 448

Reservoir capacity (m³x10⁶) 11

Upstream slope V
0.40

Forming of upstream face (code) (1)
(1)

Downstream slope 0.77

Forming of downstream face (code) (1)

Spillway slope 0.77

Forming of spillway face (code) (1)

Depth of layers (mm) 250

Depth of lifts (mm) 1000

Cement content (kg/m³) 91

Pozzolan content (kg/m³) 39

Code for pozzolan (F)

RCCDAM Unique Serial No. RCCDAM0710

Completed Dam



RCCDAM0710CD

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines