

Dam: Meander

Country: Australia

River: Meander

41°41'30.12"S 146°37'13.66"E

-41.691700 146.620468

Owner/Client: Rivers and Water Supply Commission, Tasmania

Designer/Engineer: Hydro Tasmania Consulting

Contractor: McConnell Dowell Constructors, Australia

Purpose (code): I W

Site start: 01.01.2006

RCC start: 16.01.2007

RCC completion: 31.08.2007

Site completion: 30.12.2007

Height (m): 47

Length (m): 180

Volume of RCC ($m^3 \times 10^3$): 85

Total volume ($m^3 \times 10^3$): 85

Reservoir capacity ($m^3 \times 10^6$): 43

Upstream slope: V

Forming of upstream face (code): (4)

Downstream slope: 0.70

Forming of downstream face (code): (10)

Spillway slope: 0.70

Forming of spillway face (code): (10)

Depth of layers (mm): 300

Depth of lifts (mm): 300

Cement content (kg/m^3): 70

Pozzolan content (kg/m^3): 0

Code for pozzolan: (-) -

RCCDAM Unique Serial No.: RCCDAM0388

Under Construction



RCCDAM0388UC

Completed Dam



RCCDAM0388CD

Google Earth



RCCDAM0388GE

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines