

Dam: Valsamiotis

Country: Greece

River: Valsamiotis

35°26'30.38"N 23°53'12.63"E

35.441772 23.886843

Owner/Client: Crete Development Organisation

Designer/Engineer: Hydro-Systema Ltd

Contractor: J & P Avax

Purpose (code): I

Site start: 01.10.2005

RCC start: 01.05.2007

RCC completion: 30.12.2010

Site completion: 30.12.2014

Height (m): 63

Length (m): 335

Volume of RCC (m³x10³): 640

Total volume (m³x10³): 820

Reservoir capacity (m³x10⁶): 6

Upstream slope: 0.80

Forming of upstream face (code): (13)

Downstream slope: 0.80

Forming of downstream face (code): (3)

Spillway slope: 0.80

Forming of spillway face (code): (1) *

Depth of layers (mm): 300

Depth of lifts (mm): 300

Cement content (kg/m³): 60

Pozzolan content (kg/m³): 0

Code for pozzolan: (-)

RCCDAM Unique Serial No.: RCCDAM0476

Guide to Abbreviations

Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
 - ' GEVR/GE-RCC
 - * Stepped face

Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines