

Dam: Xibingxi

Country: China

River: Longshanxi

DMS Co-ordinates: Unknown

DD Co-ordinates: Unknown

Owner/Client: Department of Electric Power, Lonyan City, Fujian Province

Designer/Engineer: Department of Water Conservancy, Qinghua University

Contractor: Gezhouba Construction Bureau

Purpose (code): H W

Site start: 18.08.1993

RCC start: 01.12.1994

RCC completion: 01.07.1995

Site completion: 01.10.1995

Height (m): 64

Length (m): 93

Volume of RCC ( $m^3 \times 10^3$ ): 25

Total volume ( $m^3 \times 10^3$ ): 33

Reservoir capacity ( $m^3 \times 10^6$ ): 9

Upstream slope: V  
0.08

Forming of upstream face (code): (4)  
(4)

Downstream slope: 0.65

Forming of downstream face (code): (3)

Spillway slope: ogee  
0.65

Forming of spillway face (code): (13)

Depth of layers (mm): 300 -  
350

Depth of lifts (mm): 300 -  
350

Cement content ( $kg/m^3$ ): 80  
79

Pozzolan content ( $kg/m^3$ ): 120  
105

Code for pozzolan: (F)

RCCDAM Unique Serial No.: RCCDAM0156

## Completed Dam



RCCDAM0156CD

# Guide to Abbreviations

## Purpose

- E Environmental
- F Flood control
- G Groundwater recharge
- H Flood control
- I Irrigation
- N Navigation
- P Pollution control
- R Recreation
- W Water supply

## Facing method

- (1) Traditional concrete against formwork
- (2) Traditional concrete against formwork with external geomembrane
- (3) RCC against formwork
- (4) RCC against formwork with external geomembrane
- (5) Traditional concrete against precast concrete panels
- (6) Traditional concrete against precast concrete panels with geomembrane
- (7) RCC against precast concrete panels
- (8) RCC against precast concrete panels with geomembrane
- (9) RCC against precast concrete panels with hot poured membrane
- (10) RCC against precast concrete blocks
- (11) Reinforced conventional concrete cast before RCC placement
- (12) Reinforced conventional concrete cast after RCC placement
- (13) Reinforced concrete cast against precast units or slip-formed facing elements
- (14) Slip-formed/extruded facing elements
- (15) RCC supported by fill shoulders
- (16) Mechanically compacted unformed face of RCC
- (17) Unformed face of RCC
  - ' GEVR/GE-RCC
  - \* Stepped face

## Pozzolans

- (-) No Pozzolan Used
- (C) High-lime flyash (ASTM Class C)
- (F) Low-lime flyash (ASTM Class F)
- (M) Milled sand
- (N) Natural pozzolan (ASTM Class N)
- (R) ROLAC (mixture of flyash and slag with or without limestone fines)
- (S) Ground-granulated blast-furnace slag
- (L) Mixture of GGBFS and limestone fines